



Release Notes

Product

VERSION: 1.14 – Release date 4/15/09

PART # / CSUM:

COMPATIBILITY: V1.10, V1.13

NEW FEATURES: WCP – “Window Lock” check box (position & control)
WCP – Window “Aspect Ratio Lock” check box
WCP and telnet/serial password protection control (on/off) default =”off”
New Host Timings
Wplist command shows image settings
Auto-restart on boot failure

CHANGES: **The following changes are included in this release.**
Sharpness setting defaults to “9”
New timings added (62-84)

BUG FIXES: **The following bug fixes are included in this release.**
Locked window moves on full screen of another window
Media Wall unable to save timing configuration for YUV
Sharpness not saved in Preset for inputs 5 and 6

ANOMALIES: **The following discrepancies are known in this release**
OPREF EDID will not work reliably if output cable is removed and plugged in within 1 second. **Wait at least 1 second between disconnect and re-plug.**
Change Administrator Password and *Password Protection* cannot be set from WCP. They can be set via RS-232 or Telnet command line entries.
For analog RGB, for both timings:
#43 1280x720_24hz
#44 1280x720_30p
Picture is left shifted and compressed into the first 20% of the screen.
3-wire & 4-wire sync don't work at 1600x1200 & 1920x1200 output
YUV window when zoomed in (RGB and DVI are OK), the first recall will always set the window to full image, the second recall will set the window to the correct zoomed portion